

BigTwin SuperServer SYS-621BT-HNC8R



More details here

Key Applications


Hyperconverged Infrastructure, Scale-Out File Storage, Container Storage,

Key Features


- Socket E (LGA 4677) support 5th/4th Gen Intel® Xeon® Scalable processors;
- Intel® C741;
- 16 DIMM Slots supporting up to 4TB of memory; ECC RDIMMs up to DDR5-5600;
- Optional M.2 NVMe Boot Controller via SCC-A2NM2241G3-B1; 2 PCIe 5.0 x16 (LP) slot; Tool-less support; Internal PCIe 4.0 x8 for 2 M.2 NVMe support onboard;
- Network connectivity via AIOM (OCP 3.0 compliant);
- Built-in SAS3 Support via Broadcom 3808; IT Mode; 3 hot-swap 3.5" drive bays (2x PCIe 5.0 NVMe/SAS and 1x PCIe 4.0 NVMe/SAS);
- Liquid Cooling Support; 4 cooling fans per 2U enclosure, 14.9K RPM; Shared Cooling Design;
- 3000W Redundant Power Supplies Titanium Level (96%+); Shared Power Design;



Form Factor	2U Rackmount Enclosure: 449 x 88 x 774mm (17.68" x 3.47" x 30.5") Package: 626 x 248 x 1150mm (24.65" x 9.76" x 45.28")
Processor	Dual Socket E (LGA-4677) 5th Gen Intel® Xeon®/4th Gen Intel® Xeon® Scalable processors Supports Intel Xeon CPU Max Series with high bandwidth memory (HBM) Up to 64C/128T; Up to 320MB Cache per CPU
System Memory	Slot Count: 16 DIMM slots Max Memory (1DPC): Up to 4TB 5600MT/s ECC DDR5 RDIMM
Drive Bays	3x 3.5" hot-swap NVMe/SAS drive bays (2x PCI-E 5.0 NVMe/SAS and 1x PCI-E 4.0 NVMe/SAS) 2 M.2 NVMe
Expansion Slots	2 PCIe 5.0 x16 LP slot(s)
On-Board Devices	SAS: SAS3 (12Gbps) via Broadcom® 3808 (IT mode) Chipset: Intel® C741 Network Connectivity: Via AIOM IPMI: Support for Intelligent Platform Management Interface v.2.0 IPMI 2.0 with virtual media over LAN and KVM-over-LAN support
Input / Output	LAN: 1 RJ45 Dedicated BMC LAN port USB: 2 USB 3.1 port(s) (2 rear) Video: 1 VGA port(s) Others: 2x M.2 for boot drive or caching M.2 form factor: NVMe double-sided 22x110mm Note: Enterprise-grade M.2 only for caching application



Drive Bay (Node A-D)	Description
1 - 11	2x 3.5" Hot-Swap NVMe Gen5 (CPU1)/SAS Drive Bays
12	1x 3.5" Hot-Swap NVMe Gen4 (CPU2)/SAS Drive Bays



Slot (Node A-D)	Description
1	AVOM Slot PCIe 5.0 x16
2	PCIe 5.0 x16 Low Profile Slot
3	PCIe 5.0 x16 Low Profile Slot

CPU1 CPU2

System Cooling	Fans: 4x 14.9K RPM Heavy Duty 8cm Fan(s) Liquid Cooling: 1Direct to Chip (D2C) Cold Plate (optional)
Power Supply	3000W Redundant Titanium Level power supplies
System BIOS	BIOS Type: AMI 32MB Flash ROM
Management	Redfish API; Supermicro Server Manager (SSM); Supermicro Power Manager (SPM); Supermicro Update Manager (SUM); SuperDoctor® 5; Super Diagnostics Offline ; KVM with dedicated LAN ; IPMI 2.0
PC Health Monitoring	FAN: Fans with tachometer monitoring Status monitor for speed control Pulse Width Modulated (PWM) fan connectors Temperature: Monitoring for CPU and chassis environment CPU: Monitors for CPU Cores, Chipset Voltages, Memory. 8+4 Phase-switching voltage regulator
Dimensions and Weight	Height: 3.47" (88 mm) Width: 17.68" (449 mm) Depth: 30.5" (774 mm) Gross Weight: 96.6 lbs (43.8 kg) Net Weight: 66.1 lbs (30 kg) Packaging: 9.76" (H) x 24.65" (W) x 45.28" (D) Available Color: Black front & silver body
Operating Environment	ROHS: RoHS Compliant Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) Non-operating Temperature: -30°C to 60°C (-22°F to 140°F) Operating Relative Humidity: 8% to 80% (non-condensing) Non-operating Relative Humidity: 8% to 90% (non-condensing)
Motherboard	Super X13DET-B
Chassis	CSE-827BQ2-R3K04P