


Storage SuperServer SSG-229J-5BE36JBF

2U front-loading all-flash storage box with 36 hot-swap E3.S NVMe bays and PCIe 5.0 with GPU/DPU support for LLM applications



Key Applications

Artificial Intelligence (AI), Big Data Analytics and AI, HPC and Big Data, Data Center Enterprise Applications, Low Power, Cost effective, NVMe Over Fabrics Solution, Large Language Model (LLM),

Key Features

- IPMI management with dedicated LAN
BF3 management with shared LAN;
- Up to 3 PCIe 5.0 x16 FHFL slots
Up to 2 DPU and 1 GPU per node;
- Up to 36 front hot-swap E3.S 1T NVMe drive bays;
- 2 Redundant 2000W Titanium Level power supplies;
- Two **hot-pluggable** systems (nodes) in a 2U form factor. Each node supports the following;



Form Factor	2U Rackmount Enclosure: 449.4 x 88 x 762mm (17.7" x 3.47" x 30") Package: 670 x 245 x 1100mm (26.37" x 9.64" x 43.3")
--------------------	---

Drive Bays Configuration	Default: Total 36 bays <ul style="list-style-type: none"> • 36 front hot-swap E3.S 1T NVMe drive bays M.2: 2 M.2 PCIe 5.0 x4 NVMe slots (M-key 2280/22110)
---------------------------------	--

Expansion Slots	Default <ul style="list-style-type: none"> • 3 PCIe 5.0 x16 FHFL slots
------------------------	--

On-Board Devices	Chipset: System on Chip Network Connectivity: 2 RJ45 1GbE with NVIDIA® ConnectX®-7 or Bluefield®-3 1 RJ45 1GbE with Realtek
-------------------------	---



System Cooling	Fans: 6 Heavy Duty 60mm Fan(s)
Power Supply	2x 2000W Redundant Titanium Level (96%) power supplies
Management	SuperCloud Composer; Supermicro Server Manager (SSM); Supermicro Update Manager (SUM); Supermicro SuperDoctor® 5 (SD5); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); SuperServer Automation Assistant (SAA) New!
Dimensions and Weight	Weight: Gross Weight: 94.8 lbs (43 kg) Net Weight: 71.88 lbs (32.6 kg) Available Color: Silver
Operating Environment	RoHS Compliant Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) Non-operating Temperature: -40°C to 60°C (-40°F to 140°F) Operating Relative Humidity: 8% to 90% (Non-Condensing) Non-operating Relative Humidity: 5% to 95% (Non-Condensing)
Motherboard	Super BPN-NVME5-229PL-J
Chassis	CSE-229ES-R000RCNDP